



Flat Polymero

311526.002.6 | Ceiling and wall luminaires

Ceiling and wall luminaires
4051859072874
LED
D 620, H 160



Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser: plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface).

Colour

Colour white

Dimensions

Diameter D 620 mm
Height H 160 mm
Weight 4 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Colour consistency (McAdam) 4
Lifetime 50000 h (L80/B10)
Photobiological safety according to EN 62471 Risk group 0

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 2.650 lm
Glare evaluation UGR (4H 8H) 1 18,2
Beam angle 117°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	15
Luminaires on B16A fuse	25
Luminaires on C10A fuse	26
Luminaires on C16A fuse	42
Inrush current / inrush current duration	10 A / 50 µs
Ripple current / Flicker	1 %
System power	24 W
Luminaire efficacy	111 lm/W
Power factor	0,95

Approbations

Type of Protection	IP 40
Protection Class	I
Glow Wire Test	850°C - 30 seconds
Impact Protection	IK10 (20 Joule)
Safety marks	F-mark
ULOR	7,5 %
Handelszeichen	CE
CIE Flux Code / CEN Flux Code	43 72 91 93 100
Energy efficiency class LED	A++
Energy class of included lamp	A++