



Flat Polymero

312096.002.4 | Ceiling and wall luminaires

Ceiling and wall luminaires
4051859161516
LED
D 620, H 160



Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser: plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface).

Colour

Colour white

Dimensions

Diameter D 620 mm
Height H 160 mm
Weight 4,02 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 83
Colour consistency (McAdam) 3
Lifetime 50000 h (L70/B10)

Lighting technology

Beam Angle 120°
Photobiological safety according to EN 62471 Risk group 1

Electrical

Control gear	Converter not necessary
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	53
Luminaires on B16A fuse	85
Luminaires on C10A fuse	53
Luminaires on C16A fuse	85
Inrush current / inrush current duration	0,2 A / 10000 µs
Colour temperature 1	4.000 K
System power 1	33 W
Rated luminous flux 1	3.250 lm
Glare evaluation UGR (4H 8H) 1	19,1
Luminaire efficacy 1	99 lm/W

Approbations

Type of Protection	IP 40
Protection Class	I
Glow Wire Test	850°C - 30 seconds
Impact Protection	IK10 (20 Joule)
Safety marks	F-mark
Other Marks	WEEE mark
Energy efficiency class LED	A+
Energy class of included lamp	A+