



# Baleva

## 451203.002.1 | Linear luminaires

Ceiling and wall luminaires  
4051859180630  
LED  
L 1200, B 46, H 60



Linear luminaire with timeless functional design. Ideal for sanitary areas, corridors, waiting areas, nursing homes, patient rooms. Body and end caps made of white plastic. Diffuser: plastic (polycarbonate), opal, shockproof. Homogeneous and smooth light distribution. Diffuser can be assembled without the use of tools. Quick and easy to install. Can be installed horizontally and vertically. 2 central cable inlets for looping the cable. Converter integrated and encapsulated.

### Colour

Colour white

### Dimensions

Length L 1.200 mm  
Width B 46 mm  
Height H 60 mm  
Weight 875 g

### Lamp

Lamp LED  
Colour temperature 4000K  
Colour rendering index (CRI) 80  
Lifetime 50000 h (L80/B10)  
Photobiological safety according to EN 62471 Risk group 0

### Lighting technology

Colour temperature 4.000 K  
Rated luminous flux 2.050 lm  
Glare evaluation UGR (4H 8H) 1 23,7  
Beam angle 150° / 107°

### Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	10
Luminaires on B16A fuse	16
Luminaires on C10A fuse	20
Luminaires on C16A fuse	32
Inrush current / inrush current duration	5 A
System power	19 W
Luminaire efficacy	108 lm/W

### Approbations

Type of Protection	IP 40, IP 44
Anmerkung Schutzart	IP 40 Ceiling mounting, IP 44 wall mounting
Protection Class	II
Glow Wire Test	650°C - 30 seconds
Impact Protection	IK07 (2 Joule)
Ambient temperature min.	-30 °C
Ambient temperature max.	40 °C
ULOR	18,1 %
Handelszeichen	CE
CIE Flux Code / CEN Flux Code	39 68 88 82 100
Energy efficiency class LED	A+
Energy class of included lamp	A+