


Industrial Hall Midi

921493.003.76 | Highbay luminaires

Highbay luminaires
4051859219477
LED
D 570, H 548



Round highbay luminaire for chain or cable suspension. Housing: die-cast aluminium with eye ring, powder-coated. Diffuser made of clear, non-reflecting, single pane safety glass (toughened glass). Refractor: PMMA, transparent. Primary light control with high-performance wide-area LED. Easy to install thanks to 1-point suspension. Suitable for chain or steel cable suspension (provided by the client). Dimming range 10% to 100%. Luminaires with limited surface temperature in accordance with DIN EN 60598-2-24 for use in environments in which a deposit of conductive dust on the luminaire can be expected.

Colour

Colour black

Dimensions

Diameter D 570 mm
Height H 548 mm
Weight 9,32 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Colour consistency (McAdam) 6
Lifetime 50000 h (L70/B10)
Photobiological safety according to EN 62471 Risk group 0

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 15.300 lm
Glare evaluation UGR (4H 8H) 1 13,9
Beam angle 70°

Electrical

Control gear DALI
Voltage 230 V / 50 Hz
Luminaires on B10A fuse 2
Luminaires on B16A fuse 4
Luminaires on C10A fuse 4
Luminaires on C16A fuse 7
Inrush current / inrush current duration 50.2 A
System power 139 W
Luminaire efficacy 111 lm/W

Approbations

Type of Protection IP 65
Protection Class I
Glow Wire Test 650°C - 30 seconds
Impact Protection IK03 (0,35 Joule)
Safety marks D-mark, F-mark
ULOR 5,7 %
Trade mark CE
CIE Flux Code / CEN Flux Code 87 97 99 94 100
Energy efficiency class LED A+
Energy class of included lamp A+

Accessories

982112.003 Ceiling and wall mounting bracket L 394, B 124, H 232