



Less is more 27

312200.002.1.76 | LED linear systems

Ceiling and wall luminaires
 4051859231943
 LED
 L 1512, B 28, H 38



Ceiling and wall luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. Diffuser: plastic (non-yellowing PMMA), opal. Suitable for Ceiling mounting, Wall (surface). External driver with connecting cable.

Colour

Colour white

Dimensions

Length L 1,512 mm
 Width B 28 mm
 Height H 38 mm
 Weight 1,47 kg

Lamp

Lamp LED
 Colour temperature 4000K
 Colour rendering index (CRI) 82
 Colour consistency (McAdam) 3
 Lifetime 60000 h (L80/B10)
 Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
 Rated luminous flux 2.900 lm
 Glare evaluation UGR (4H 8H) 1 28,2
 Beam angle 110° / 114°

Electrical

Control gear Voltage converter, DALI dim.
 Voltage 220 - 240 V / 50 - 60 Hz
 Luminaires on B10A fuse 9
 Luminaires on B16A fuse 15
 Inrush current / inrush current duration 43 A / 160 µs
 System power 39 W
 Luminaire efficacy 75 lm/W
 Power factor 0,95

Approbations

Type of Protection IP 20
 Protection Class II
 Glow Wire Test 650°C - 30 seconds
 Safety marks F-mark
 ULOR 0
 Handelszeichen CE
 CIE Flux Code / CEN Flux Code 48 79 96 100 100
 Energy efficiency class LED A++
 Energy class of included lamp A++