



Less is more 27

312200.002.1.76 | LED linear systems

Ceiling and wall luminaires
4051859231943
LED
L 1512, B 28, H 38



Housing extruded aluminium profile powder-coated. End caps die-cast aluminium powder-coated. Diffuser plastic (PMMA), opal. External converter with connecting cable. Lamps (LED) included in delivery.

Colour

Colour white

Dimensions

Length L 1.512 mm
Width B 28 mm
Height H 38 mm
Weight 1,47 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 82
Colour consistency (McAdam) 3
Lifetime 60000 h (L80/B10)

Lighting technology

Beam Angle 110°/114°
Photobiological safety according to EN 62471 Risk group 1

Electrical

Control gear	Voltage converter, DALI dim.
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	9
Luminaires on B16A fuse	15
Inrush current / inrush current duration	43 A / 160 µs
Colour temperature 1	4.000 K
System power 1	39 W
Rated luminous flux 1	2.900 lm
Glare evaluation UGR (4H 8H) 1	28,2
Luminaire efficacy 1	75 lm/W

Approbations

Type of Protection	IP 20
Protection Class	II
Glow Wire Test	650°C - 30 seconds
Safety marks	F-mark
Other Marks	WEEE mark
Energy efficiency class LED	A++
Energy class of included lamp	A++