



Hemis Round

312185.002.1 | Surface mounted modular luminaires

Ceiling luminaires
4051859223757
LED
D 300, H 33



Glare-free LED ceiling luminaire with optical lens system. Base: metal, powder-coated, with bayonet fixing. Housing: plastic (polycarbonate). Housing and diffuser are screwed together. Diffuser with optic lenses. Easy installation with Plug & Play plug connection. Thanks to UGR < 22 ideal for corridors, stairways, shops, schools, meeting rooms, rest areas.

Colour

Colour white

Dimensions

Diameter D 300 mm
Height H 33 mm
Weight 1,06 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Lifetime 40000 h (L80/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 1.800 lm
Glare evaluation UGR (4H 8H) 1 20,6
Beam angle 68°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 Hz
Luminaires on B10A fuse	20
Luminaires on B16A fuse	32
Luminaires on C10A fuse	34
Luminaires on C16A fuse	40
Inrush current / inrush current duration	73.6 A / 25 µs
System power	15 W
Luminaire efficacy	120 lm/W

Approbations

Type of Protection	IP 40
Protection Class	I
Glow Wire Test	850°C - 30 seconds
Impact Protection	IK06 (1 Joule)
Safety marks	F-mark
ULOR	0
Handelszeichen	CE
CIE Flux Code / CEN Flux Code	86 99 100 100 100
Energy efficiency class LED	A++
Energy class of included lamp	A++