

# 311328.982.1.76



Series: Flat Polymero Kreis XXL Pendant luminaires

Type of Installation: Pendant  
 Type of Protection: IP 40  
 Protection Class: I  
 Lamp: 6 x TC-L 55 W  
 Dimensions: D 1040, H 150  
 Colour: white

Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic (polycarbonate). Diffuser fastening: sash lock.

### Electro-technics:

Control gear EB DALI  
 Voltage 220 - 240 V / 0 Hz, 50 - 60 Hz  
 Luminaires on B10A fuse 2  
 Luminaires on B16A fuse 4  
 Inrush current / inrush current duration 135 A

### Testings:

Type of Protection IP 40  
 Glow Wire Test 850°C - 30 seconds  
 Safety marks F-mark  
 Other Marks WEEE mark  
 Protection Class I  
 Impact Protection IK10 (20 Joule)  
 Country Code CE  
 Energy efficiency class A, A+  
 conventional lamp

### Lamp 1:


Number of lamps 6  
 Lamp TC-L  
 Wattage 55 W  
 Socket 2G11  
 Lifetime

### Weights and measures:

Diameter D 1.040 mm  
 Height H 150 mm  
 Suspension length 600-1300 mm  
 Ceiling thickness  
 Weight 16,1 kg

### Lighting technology:

UGR 18,7  
 Luminaire beam angle 116°  
 Light Output Ratio 55,4 %



### Replacement parts

#### Replacement diffusers

08-311292.012 D 1040, H 150