



Ring of Fire

311570.004.76 | Pendant luminaires

Pendant luminaires
4010319993630
LED
D 690, H 81



Supporting ring: aluminium. Hand-blown opal glass, satin finish.
Canopy: aluminium. Adjustable suspension steel cable. LED included.

Colour

Colour aluminium , anodised

Dimensions

Diameter D 690 mm
Height H 81 mm
Suspension length 500-1200 mm
Weight 7,22 kg

Lamp

Lamp LED
Colour temperature 3000K
Colour rendering index (CRI) 80
Colour consistency (McAdam) 3
Lifetime 50000 h (L70/B10)

Lighting technology

Beam Angle 114°
Photobiological safety according to EN 62471 Risk group 1

Electrical

Control gear DALI
Voltage 220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse 13
Luminaires on B16A fuse 20
Inrush current / inrush current duration 30 A / 200 µs
Ripple current / Flicker 1 %
Colour temperature 1 3.000 K
System power 1 39 W
Rated luminous flux 1 3.800 lm
Glare evaluation UGR (4H 8H) 1 22,3
Luminaire efficacy 1 98 lm/W

Approbations

Type of Protection IP 20
Protection Class I
Glow Wire Test 960°C - 30 seconds
Impact Protection IK02 (0,20 Joule)
Safety marks F-mark
Other Marks WEEE mark
Energy efficiency class LED A++
Energy class of included lamp A++