



Lightstream LED Mini

722144.114 | Spotlights

Spotlights
4051859428404
LED
L 315, B 276, H 180



LED floodlight for accent and area lighting. Housing made of corrosion-resistant die-cast aluminium for outdoor use, powder-coated. Bracket: aluminium, powder-coated. Tilt angle can be adjusted with angular scale. With membrane valve as a standard to prevent condensed water. Asymmetrical area flood reflector of MIRO-SILVER® with reflex-boosted coating. COB-LEDs with socket, selection of light colour 830 or 840. Toughened glass cover. Asymmetrical light distribution. Quick connection possible without opening the housing by screw-less plug connector on bayonet locked slide. Piano-key terminal up to 5 x 2,5 mm², max cable Ø 13 mm. Windage area $A_w = 0,023 \text{ m}^2$.

Colour

Colour silver metallic

Dimensions

Length L 315 mm
Width B 276 mm
Height H 180 mm
Weight 3,4 kg

Lamp

Lamp LED
Colour temperature 3000K
Colour rendering index (CRI) 80
Colour consistency (McAdam) 3
Lifetime 50000 h (L80/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 3.000 K
Rated luminous flux 3.200 lm
Glare evaluation UGR (4H 8H) 1 38,6
Beam angle 63° / 43° / 0° / 43°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	31
Luminaires on B16A fuse	50
Luminaires on C10A fuse	52
Luminaires on C16A fuse	85
Inrush current / inrush current duration	5 A / 50 µs
Ripple current / Flicker	20 %
System power	25 W
Luminaire efficacy	128 lm/W
Power factor	0,95

Approbations

Type of Protection	IP 65
Protection Class	I
Glow Wire Test	650°C - 30 seconds
Impact Protection	IK04 (0,50 Joule)
Safety marks	D-mark, F-mark
Ambient temperature min.	-25 °C
Ambient temperature max.	42 °C
ULOR	0
Trade mark	CE
CIE Flux Code / CEN Flux Code	29 69 96 100 100
Energy efficiency class LED	A++
Energy class of included lamp	A++

Accessories

982047.000	Pole tops L 250, B 95, H 153 for spigot 60 mm, uncoated
982047.004	Pole tops L 250, B 95, H 153 for spigot 60 mm, silver metallic
982048.000	Pole tops L 250, B 95, H 153 for spigot 76 mm, uncoated
982048.004	Pole tops L 250, B 95, H 153 for spigot 76 mm, silver metallic
982049.000	Pole tops L 250, B 114, H 153 for spigot 60 mm, uncoated
982049.004	Pole tops L 250, B 114, H 153 for spigot 60 mm, silver metallic
982050.000	Pole tops L 250, B 114, H 153 for spigot 76 mm, uncoated
982050.004	Pole tops L 250, B 114, H 153 for spigot 76 mm, silver metallic
982092.000	Pole clip L 178, B 174, H 38 for pole diameter 95 - 114 mm
982093.000	Pole clip L 178, B 194, H 38 for pole diameter 115 - 135 mm
982086.000	Wall bracket L 1000, B 180, H 180 Overall length 1000 mm, uncoated
982058.000	Wall bracket L 500, B 180, H 180 Overall length 500 mm, uncoated
982524.004	Adapter set for pole attachments L 365, B 365, H 55 Adapter set for 4-fold configuration (4 x 90°), silver metallic
982638.003	Junction box L 78, B 53, H 28