



Brick EVO

581632.0031.1 | Wall luminaires

Wall luminaires
4051859113768
LED
L 120, B 120, H 24



Flat surface-mounted LED fitting for illumination of wall related areas such as stairs, ramps or corridors. Housing made of corrosion-resistant die-cast aluminium, powder-coated. Diffuser with clear toughened glass. With compensation for drill hole deviations. Integral driver. With connecting terminal up to 1 x 3 x 1.5 mm², for max. 13 mm diameter mains cable.

Colour

Colour anthracite metallic

Dimensions

Length L 120 mm
Width B 120 mm
Height H 24 mm
Weight 404 g

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Lifetime 50000 h (L80/B10)

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 55 lm
Glare evaluation UGR (4H 8H) 1 29,1
Beam angle 45° / 90° / 0° / 90°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	30
Luminaires on B16A fuse	40
Inrush current / inrush current duration	17.3 A / 34 μs
System power	4 W
Luminaire efficacy	14 lm/W

Approbations

Type of Protection	IP 65
Protection Class	I
Glow Wire Test	960°C - 30 seconds
Impact Protection	IK09 (10 Joule)
Safety marks	F-mark
ULOR	3,9 %
Handelszeichen	CE
CIE Flux Code / CEN Flux Code	53 82 95 96 100
Energy efficiency class LED	A+
Energy class of included lamp	A+